


ABS-Vario



Shuttering profile profiled on one side. Profile for shuttering concreting sections, end formwork for slabs and walls, shuttering of bridge superstructure cantilevers with reinforcement penetration, available drilled and/or slotted. Bridging of formwork joints. ABS vario profiles are also used to create Quick ASS recesses.

ABS-Vario

Article number	Title of variant	Length m	B mm	b mm	h mm	Packaging piece/pallet	Packaging metre/pallet	Weight kg/metre
12624000	ABS- 60 Vario, L = 120 cm	1,200	8	12	60	780	936	1,900
12625000	ABS- 80 Vario, L = 120 cm	1,200	8	12	80	600	720	2,800
12626000	ABS-100 Vario, L = 120 cm	1,200	8	12	100	420	504	3,500
12627000	ABS-150 Vario, L = 120 cm	1,200	8	12	150	300	360	5,600
12628000	ABS-160 Vario, L = 120 cm	1,200	8	18	160	300	360	6
12629000	ABS-180 Vario, L = 120 cm	1,200	8	18	180	240	288	6,400
12630000	ABS-200 Vario, L = 120 cm	1,200	8	18	200	240	288	7
12630100	ABS-220 Vario, L = 120 cm	1,200	10	18	220	180	216	9
12630400	ABS-230 Vario, L = 120 cm	1,200	10	18	230	180	216	10,500
12631000	ABS-240 Vario, L = 120 cm	1,200	10	18	240	180	216	12
12632000	ABS-250 Vario, L = 120 cm	1,200	10	18	250	180	216	12,200
12632400	ABS-280 Vario, L = 120 cm	1,200	10	18	280	120	144	12,800
12633000	ABS-300 Vario, L = 120 cm	1,200	10	18	300	120	144	13,200
12634000	ABS-350 Vario, L = 120 cm	1,200	12	22	350	120	144	14,100
12635000	ABS-400 Vario, L = 120 cm	1,200	13	22	400	120	144	15

ABS-Vario

Article number	Title of variant	Length m	B mm	b mm	h mm	Packaging piece/pallet	Packaging metre/pallet	Weight kg/metre
12636000	ABS-450 Vario, L = 120 cm	1,200	13	22	450	60	72	16,700