


Montage-Supo



The mounting suppo is used to fix the mounting reinforcement. The mounting suppo is nailed to the formwork using the factory-fitted aluminum nail. The reinforcement bar (Ø 3-18 mm) is simply inserted into the plastic clip. This enables the reinforcement to be set up quickly. Thanks to the specially designed shape of the clip, the Supo clamps optimally to the reinforcing steel.

Article number	Title of variant	Length mm	Concrete cover mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22112000	Mounting Supo MSB 30 N with studs, DBV-30-L2/F/T/A/D3-18	75	30	300 pieces/carton	5,600	12.000
22113000	Mounting Supo MSB 35 N with studs, DBV-35-L2/F/T/A/D3-18	75	35	200 pieces/carton	7,500	8.000
22114000	Mounting Supo MSB 40 N with studs, DBV-40-L2/F/T/A/D3-18	75	40	200 pieces/carton	8	8.000
22115000	Mounting Supo MSB 45 N with studs, DBV-45-L2/F/T/A/D3-18	75	45	175 pieces/carton	9,100	7.000
22116000	Mounting Supo MSB 50 N with studs, DBV-50-L2/F/T/A/D3-18	75	50	150 pieces/carton	10	6.000
22117000	MSB other dimensions					