


Kapo with studs



The Kapo is mainly mounted on standing reinforcement. Installation is possible on reinforcement Ø 3-10 mm. To prevent twisting, the Kapo is mounted on a reinforcement crossing point. The spring steel clamp Ø 2 mm clamps the Kapo optimally to the reinforcing steel. Quick installation is guaranteed. The studded contact surface produces a very good exposed concrete surface. The concrete can also be supplied in other colors on request.

Kapo with studs

Article number	Title of variant	Length mm	Concrete cover mm	Packaging piece/ metre/ metre by the bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22118300	Kapo 25/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	30	25	500 pieces/bag	3,600	10.000
22119300	Kapo 30/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	30	30	500 pieces/bag	4,200	10.000
22120300	Kapo 35/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	30	35	500 pieces/bag	5,100	10.000
22121300	Kapo 40/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	35	40	250 pieces/bag	6,800	5.000
22122300	Kapo 45/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	35	45	250 pieces/bag	8,100	5.000
22123300	Kapo 50/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	40	50	200 pieces/bag	10,500	4.000
22124300	Kapo 55/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	40	55	175 pieces/bag	12,200	3.500
22125300	Kapo 60/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	40	60	150 pieces/bag	14,400	3.000
22126300	Kapo 65/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	50	65	125 pieces/bag	17	2.500
22127300	Kapo 70/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	50	70	100 pieces/bag	19,700	2.000