


Elevation BWA



The BWA is mounted at the end of the reinforcement. Installation is possible on reinforcement Ø 3-10 mm. The plastic clip ensures a secure hold. The insertion depth is 20 mm.

Article number	Title of variant	Concrete cover mm	H mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22610000	Elevation BWA 20/3-10 (FB round Ø35 mm)	20	40	500 pieces/bag	7	12.000
22611000	Elevation BWA 25/3-10 (FB round Ø35 mm)	25	45	500 pieces/bag	7,900	12.000
22612000	Elevation BWA 30/3-10 (FB round Ø35 mm)	30	50	500 pieces/bag	8,800	10.000
22613000	Elevation BWA 35/3-10 (FB round Ø35 mm)	35	55	400 pieces/bag	9,600	8.000
22614000	Elevation BWA 40/3-10 (FB round Ø35 mm)	40	60	400 pieces/bag	10,500	8.000
22615000	Elevation BWA 45/3-10 (FB round Ø35 mm)	45	65	250 pieces/bag	11,400	6.000
22616000	Elevation BWA 50/3-10 (FB round Ø35 mm)	50	70	250 pieces/bag	12,300	6.000
22617000	BWA special sizes/3-10					