


Kapo clamps



The Kapo is mainly mounted on standing reinforcement. Installation is possible on reinforcement $\varnothing$ 3-10 mm. To prevent twisting, the Kapo is mounted on a reinforcement crossing point. The two spring steel clamps $\varnothing$ 2 mm clamp the Kapo optimally to the reinforcing steel. Quick installation is guaranteed. Due to the small contact surface, a very good exposed concrete surface is achieved. The concrete can also be supplied in other colors on request.

Kapo clamps

Article number	Title of variant	Length mm	Concrete cover mm	Packaging piece/ metre/ metre by the bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22118400	Kapo 25/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	30	25	500 pieces/bag	3,600	10.000
22119400	Kapo 30/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	30	30	500 pieces/bag	4,200	10.000
22120400	Kapo 35/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	30	35	500 pieces/bag	5,100	10.000
22121400	Kapo 40/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	35	40	250 pieces/bag	6,800	5.000
22122400	Kapo 45/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	35	45	250 pieces/bag	8,100	5.000
22123400	Kapo 50/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	40	50	200 pieces/bag	10,500	4.000
22124400	Kapo 55/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	40	55	175 pieces/bag	12,200	3.500
22125400	Kapo 60/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	40	60	150 pieces/bag	14,400	3.000
22126400	Kapo 65/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	50	65	125 pieces/bag	17	2.500
22127400	Kapo 70/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	50	70	100 pieces/bag	19,700	2.000