


Clipo for Ø12-14mm



The Clipo /14 is clipped onto standing reinforcement. The plastic clip can be clipped onto reinforcing steel Ø 12-14 mm. Quick installation is guaranteed. The Clipo is the ideal spacer when, for example, the reinforcement cage is embedded in the formwork (e.g. diaphragm walls) or when the formwork is slid over the reinforcement cage (column formwork, cardboard formwork tubes or concrete pipes and shaft structures). The Clipo can also be supplied with two clamps mounted on both sides as an option. The minimum width of the Clipo is then 50 mm (wider widths are also available on request).

Article number	Title of variant	Concrete cover mm	Width B mm	L mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22146100	Clipo 30/14 for Ø 12-14 mm	30	76	25	200 pieces/carton	18	4.050
22147100	Clipo 35/14 for Ø 12-14 mm	35	86	25	121 pieces/carton	21,900	3.150
22148100	Clipo 40/14 for Ø 12-14 mm	40	96	25	100 pieces/carton	27,100	2.610
22149100	Clipo 45/14 for Ø 12-14 mm	45	106	25	80 pieces/carton	36	2.070
22150100	Clipo 50/14 for Ø 12-14 mm	50	116	25	70 pieces/carton	49	1.800
22151100	Clipo 55/14 for Ø 12-14 mm	55	126	25	64 pieces/carton	56,900	1.440
22152100	Clipo 60/14 for Ø 12-14 mm	60	136	25	50 pieces/carton	62,100	1.260
22153100	Clipo 70/14 for Ø 12-14 mm	70	156	25	42 pieces/carton	78	900
22154300	Supplement 2 staples Clipo /14 (min. Clipo cutting length = 50 mm)						