


## Clipo for Ø16-20mm



The Clipo /20 is clipped onto standing reinforcement. The plastic clip can be clipped onto reinforcing steel Ø 16-20 mm. Quick installation is guaranteed. The Clipo is the ideal spacer when, for example, the reinforcement cage is embedded in the formwork (e.g. diaphragm walls) or when the formwork is slid over the reinforcement cage (column formwork, cardboard formwork tubes or concrete pipes and shaft structures). The Clipo can also be supplied with two clamps mounted on both sides as an option. The minimum width of the Clipo is then 50 mm (wider widths are also available on request).

Article number	Title of variant	Concrete cover mm	Width B mm	L mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22148200	Clipo 40/20 for Ø 16-20 mm	40	104	25	90 pieces/carton	52	2.470
22149200	Clipo 45/20 for Ø 16-20 mm	45	114	25	75 pieces/carton	69,400	1.960
22150200	Clipo 50/20 for Ø 16-20 mm	50	124	25	70 pieces/carton	93,800	1.700
22151200	Clipo 55/20 for Ø 16-20 mm	55	134	25	50 pieces/carton	108	1.360
22152200	Clipo 60/20 for Ø 16-20 mm	60	144	25	45 pieces/carton	118,600	1.190
22153200	Clipo 70/20 for Ø 16-20 mm	70	164	25	35 pieces/carton	148,200	1.000
22154400	Surcharge 2 staples Clipo /20 (min. Clipo cutting length = 50 mm)						