


Aal N L=80 mit Noppen



The Aal 20/80 N is a surface spacer and is used, for example, in the area of ceilings and beams with horizontal reinforcement. The contact surface is dimpled. The concrete runs under the studs. Ideal for exposed concrete surfaces. The two bends make it tilt and position-proof. Quick installation is guaranteed.

Article number	Title of variant	Concrete cover mm	a mm	L mm	Packaging piece/pallet	Weight kg/100 pieces
22351000	Eel 20/80 N, L = 80 cm with knobs	20	20	800	2100	54
22352000	Aal 25/80 N, L = 80 cm with knobs	25	20	800	2000	58,600
22353000	Eel 30/80 N, L = 80 cm with knobs	30	22	800	1750	60
22354000	Eel 35/80 N, L = 80 cm with knobs	35	22	800	1380	76,100
22355000	Eel 40/80 N, L = 80 cm with knobs	40	25	800	1000	83
22356000	Aal 45/80 N, L = 80 cm with knobs	45	25	800	1000	95
22357000	Eel 50/80 N, L = 80 cm with knobs	50	25	800	800	110
22358000	Eel 55/80 N, L = 80 cm with knobs	55	25	800	700	123
22359000	Eel 60/80 N, L = 80 cm with knobs	60	25	800	600	151