


K-TEC-3s® concrete screw



K-TEC-3s®
mit B 15 Gewinde



Kipp B 15 rund
mit S-Mutter, verzinkt



Kipp B 15 rund mit
Flügelmutter, verzinkt



K-TEC-3s® from BETOMAX® systems can be reused several times and combines the advantages of temporary machine attachment using a coarse thread with the advantages of a self-tapping concrete screw.

Diverse areas of application

for all temporary fastenings with low to medium loads, e.g. B. Machine attachments such as core drills, concrete processing machines, etc.

On the one hand: Robust B 15 formwork anchor thread enables the use of all types of locking devices: Kipp B 15 with S nut, plate wing nut or similar.

On the other hand: heavy-duty, self-tapping special thread ensures a reliable form fit in the anchoring base

Safe handling

due to the simplicity of the system with a minimum number of components

Enormous time savings

No hole cleaning required; no additional operations

Small edge and center distances can be achieved

No dowel, no spreading effect

Heavy duty

due to a perfect form fit in the anchoring base

Minimal use of tools

Cordless screwdriver recommended

Easiest control

about drill hole diameter (14 mm), depth and fully screwed in thread reusable

Depending on the substrate, up to 20 setting processes are possible; simple control with the help of a test gauge (order separately)

Comment to article

For more locking devices, see anchor technology.

